



MATERIAL SAFETY DATA SHEET

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME : LIGHTWEIGHT WALLBOARD JOINT COMPOUND
UPC NUMBER : 7079810114
PRODUCT USE/CLASS : Lightweight Joint Compound

MANUFACTURER: 24 HOUR EMERGENCY:
DAP INC. TRANSPORTATION: 1-800-535-5053 (352-323-3500)
2400 BOSTON STREET MEDICAL : 1-800-327-3874 (513-558-5111)
BALTIMORE, MD 21224

PREPARE DATE : 02/13/1996 GENERAL INFORMATION:
REVISION NO. : 8 DAP INC. : 1-888-DAP-TIPS (1-888-327-8477)
REVISION DATE: 04/25/2000

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

ITEM	CHEMICAL NAME	CAS NUMBER	WT/WT % RANGE
01	Calcium Carbonate	1317-65-3	30.0-45.0 %
02	Crystalline Silica	14808-60-7	0.1- 1.0 %
03	Amorphous Mineral Silicate	93763-70-3	5.0-10.0 %
04	Attapulgite(polygorskite)	12174-11-7	1.0- 5.0 %

ITEM	ACGIH		OSHA		COMPANY	SKIN
	TLV-TWA	TLV-STEL	PEL-TWA	PEL-CEILING	TLV-TWA	
01	10 mg/m3	N.E.	15 mg/m3	N.E.	N.E.	NO
02	0.1 mg/m3	N.E.	0.1 mg/m3	N.E.	N.E.	NO
03	10 mg/m3	N.E.	5 mg/m3	N.E.	N.E.	NO
04	N.E.	N.E.	N.E.	N.E.	N.E.	NO

(See Section 16 for abbreviation legend)

Remaining ingredients are not considered hazardous per the OSHA Hazard Communication Standard.

Listed Permissible Exposure Levels (PEL) are from the U.S. Dept. of Labor OSHA Final Rule Limits (CFR 29 1910.1000); limits may vary between states.

(Continued on Page 2)



|
| SECTION 3 - HAZARDS IDENTIFICATION |
|
|-----

EMERGENCY OVERVIEW: CAUTION! Removal of this product after use will result in the generation of dust. If dry-sanded, exposure to dust may result in build-up of material in eyes, ears, nose, and mouth which may cause irritation.

POTENTIAL HEALTH EFFECTS:

EFFECTS OF OVEREXPOSURE - EYE CONTACT: May cause eye irritation.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: May dry skin.

EFFECTS OF OVEREXPOSURE - INHALATION: Vapor may irritate nose and upper respiratory tract.

EFFECTS OF OVEREXPOSURE - INGESTION: None known.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Inhalation of dust may result in pulmonary and respiratory damages. Prolonged or repeated inhalation of dust may cause lung damage. Respirable crystalline silica dust and polygorskite fibers are considered a suspect human carcinogen by IARC. Risk to ones health depends on level and duration of exposure.

MEDICAL CONDITIONS WHICH MAY BE AGGRAVATED BY CONTACT: Asthma and asthma-like conditions may worsen from prolonged and repeated exposure.

PRIMARY ROUTE(S) OF ENTRY: SKIN CONTACT INHALATION

|
| SECTION 4 - FIRST AID MEASURES |
|
|-----

EYE CONTACT: Flush with large quantities of water until irritation subsides. Contact a physician.

SKIN CONTACT: Wash with soap and water.

INHALATION: Remove to fresh air. Contact a physician immediately.

INGESTION: DO NOT INDUCE VOMITING. Contact a physician or Regional Poison Control Center immediately.

COMMENTS: None.

(Continued on Page 3)



SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT: >200 F
(SETAFLASH CLOSED CUP)

LOWER EXPLOSIVE LIMIT: N.A.
UPPER EXPLOSIVE LIMIT: N.A.

AUTOIGNITION TEMPERATURE: N.E.

EXTINGUISHING MEDIA: CO2 DRY CHEMICAL FOAM

UNUSUAL FIRE AND EXPLOSION HAZARDS: None known.

SPECIAL FIREFIGHTING PROCEDURES: Use water spray to cool exposed surfaces.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

SPILL OR LEAK PROCEDURES: Scrape up dried material and place into containers.

SECTION 7 - HANDLING AND STORAGE

HANDLING INFORMATION: KEEP OUT OF REACH OF CHILDREN. Keep containers away from excessive heating and freezing. Avoid skin and eye contact. Do not inhale dusts of this product.

STORAGE INFORMATION: Store away from caustics and oxidizers. Keep containers tightly closed when not in use. Keep containers from excessive heat and freezing. Do not store at temperatures above 120 degrees F.

OTHER PRECAUTIONS: None.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: If dry-sanding, provide sufficient mechanical ventilation to maintain exposure below PEL and TLV.

RESPIRATORY PROTECTION: If 8 hour exposure limit or value is exceeded for any component, use an approved NIOSH/OSHA respirator. Consult your safety equipment supplier and the OSHA regulation, 29 CFR 1910.134 for respirator requirements. A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. Use an approved NIOSH/OSHA respirator if dry sanded.

EYE PROTECTION: Safety glasses with side shields recommended.

(Continued on Page 4)



SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

SKIN PROTECTION: Gloves recommended for repeated or prolonged contact with skin.

OTHER PROTECTIVE EQUIPMENT: None.

HYGIENIC PRACTICES: Remove contaminated clothing and wash before reuse.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE : 210 - 220 F VAPOR DENSITY : Is heavier than air
ODOR : Musty Odor
APPEARANCE : Gray/White Paste EVAPORATION RATE: Is slower than Butyl
SOLUBILITY IN H₂O : Soluble Acetate
SPECIFIC GRAVITY : 1.0752
VAPOR PRESSURE : 17.5 mm Hg @ 68 F
PHYSICAL STATE : Paste

(See Section 16 for abbreviation legend)

SECTION 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID: Excessive heat and freezing.

INCOMPATIBILITY: Strong oxidizers and caustics.

HAZARDOUS DECOMPOSITION PRODUCTS: Normal decomposition products, i.e. CO_x, NO_x

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

SECTION 11 - TOXICOLOGICAL PROPERTIES

No product or component toxicological information is available.

SECTION 12 - ECOLOGICAL INFORMATION

No Information.

(Continued on Page 5)



SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE MANAGEMENT/DISPOSAL: This product does not meet the definition of a hazardous waste according to U.S. EPA Hazardous Waste Management Regulations, 40 CFR Section 261. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste.

EPA WASTE CODE - If discarded (40 CFR 261): None.

SECTION 14 - TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME: Not Regulated by D.O.T.

DOT HAZARD CLASS: NONE

DOT UN/NA NUMBER: NONE PACKING GROUP: NONE

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS: AS FOLLOWS -

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

CHEMICAL NAME	CAS NUMBER	WT/WT % RANGE
---------------	------------	---------------

No SARA Section 313 components exist in this product.

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

CHEMICAL NAME	CAS NUMBER
---------------	------------

No information is available.

NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product:

CHEMICAL NAME	CAS NUMBER
Water	7732-18-5
Magnesium aluminum silicate	12174-11-7
Vinyl Acetate Polymer	25067-01-0

(Continued on Page 6)



SECTION 15 - REGULATORY INFORMATION

----- CHEMICAL NAME ----- CAS NUMBER

PENNSYLVANIA RIGHT-TO-KNOW:

The following non-hazardous ingredients are present in the product at greater than 3%:

----- CHEMICAL NAME ----- CAS NUMBER
Water 7732-18-5

CALIFORNIA PROPOSITION 65:

WARNING: The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer:

----- CHEMICAL NAME ----- CAS NUMBER
Crystalline Silica 14808-60-7
Polygorskite 12174-11-7

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: No information available.

SECTION 16 - OTHER INFORMATION

HMIS RATINGS - HEALTH: 1 FLAMMABILITY: 0 REACTIVITY: 0

PREVIOUS MSDS REVISION DATE: 01/04/2000

REASON FOR REVISION:

- SECTION 2: Changes in composition.
- SECTION 3: Additional health hazard warnings.
- SECTION 15: Updated of RTK.

VOC less water, less exempt solvent: 0.1-0.3 g/L
VOC material : 0.1-0.3 g/L

(Continued on Page 7)



SECTION 16 - OTHER INFORMATION

LEGEND: ACGIH - AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS
N.A. - NOT APPLICABLE
N.E. - NOT ESTABLISHED
PEL - PERMISSIBLE EXPOSURE LIMIT
NTP - NATIONAL TOXICOLOGY PROGRAM
SARA - SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986
STEL - SHORT TERM EXPOSURE LIMIT
TLV - THRESHOLD LIMIT VALUE(8 HR. TIME WEIGHTED AVERAGE OR TWA)
VOC - VOLATILE ORGANIC COMPOUND
NJRTK - NEW JERSEY RIGHT TO KNOW LAW
N.D. - NOT DETERMINED

MSDS# 71084

This data is offered in good faith as typical values and not as a product specification. No warranty either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review the recommendations in specific context of the intended use and determine if they are appropriate.

< End OF MSDS >